



PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1501-E SERIES

PAGE : 1/6

Index

1. Scope
2. Part name & part numbers
3. Construction. dimensions. material & surface finish
4. Ratings & applicable wires
5. Conditions
6. Performance
  - 6.1 Electrical performance
  - 6.2 Mechanical performance
  - 6.3 Environmental performance and others
7. Insertion and Withdrawal Force

			APPROVED	CHECKED	WRITTEN
			BY	BY	BY
			Jack Yin	Diankui Wan	Dengchun Yi
A0	NEW RELEASE	2021.10.26			
REV.	DESCRIPTION	DATE	DOCUMENT NO: PS-A1501-E-002		

## PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1501-E SERIES

PAGE : 2/6

## 1.SCOPE:

This specification covers the requirements for product performance of 1.50 mm pitch wire to board connector series.

## 2.PART NAME &amp; PART NUMBERS

Part name	Part number
Housing	A1501HE
Terminal	A1501-T-E
Wafer	A1501WVE A1501WRE

## 3. CONSTRUCTION. DIMENSIONS . MATERIAL &amp; SURFACE FINISH

Construction and dimensions shall be in accordance with the referenced drawings.  
Material and surface finish shall be as specified below.

Part name		Material	Surface finish
Housing		Nylon 66	UL94V-0
Terminal		Phosphor bronze	Tin over Nickel/Gold over Nickel
Wafer	Post	Brass	Tin over Nickel/Gold over Nickel
	Body	LCP/9T	UL94V-0

## 4. RATINGS &amp; APPLICABLE WIRES

Item	Standard		
Rated Voltage (Max.)	100V AC DC		Insulation O.D. 0.90mm~1.50mm
Rated Current (Max.) and Applicable Wires	AWG #24	10~30Circuits:2.0A AC DC	
		32~40Circuits:1.5A AC DC	
Ambient Temperature Range	-25℃~85℃*		

\*: Including terminal temperature rise

## PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1501-E SERIES

PAGE : 3/6

## 5. CONDITIONS:

The conditions shall be in accordance with the referenced data of next table.

Number	Item	Requirement
(1)	Bend up	2°Max.
	Bend down	3°Max.
	Twisting	2°Max.
	Rolling	5°Max.
(2)	Bell mouth (flare)	0.05-0.25 mm
(3)	Cut-off tab length	0.3 mm Max.
(4)	Extruded wire length	0.2-0.6 mm
(5)	Seam	Seam shall not be opened and no wire allowed out of crimping area
(6)	Wire strip length	2.1 mm ref.
(7)	Lance height	0.3 mm ref.

After crimping, the crimped areas [ (5)、(6) ] should be as follows.

Wire Size (AWG)	Terminal Part Number	Conductor(mm)		Insulation(mm)		Crimp Strength (kgf)
		Crimp Width	Crimp Height	Crimp Width	Crimp Height	
# 24	A1501-T-E	1.00	0.62~0.67	1.15	1.40	3.00(Min.)
# 26			0.57~0.62		1.35	2.00(Min.)
# 28			0.50~0.55		1.30	1.00(Min.)

The crimp width at the conductor part 、 crimp width & crimp height at the insulation part is a reference value, so adjust it according to a wire to be used。

## 6. PERFORMANCE

## 6.1 ELECTRICAL PERFORMANCE

Test Description		Procedure	Requirement
6-1-1	Contact Resistance	Mate connectors, measure by dry circuit, 20mV Max. 10mA. (Based upon JIS C5402 5.4)	30mΩ Max.
6-1-2	Insulation Resistance	Mate connectors, apply 500V DC between adjacent terminal or ground. (Based upon JIS C5402 5.2/MIL-STD-202 Method 302 Cond. B)	500MΩ Min.
6-1-3	Dielectric Withstanding Voltage	Mate connectors, apply 500V AC (rms) for 1 minute between adjacent terminal or ground. (Based upon JIS C5402 5.1/MIL-STD-202 Method 301)	No Breakdown

**PRODUCT SPECIFICATION**
**PRODUCT SERIES NAME: A1501-E SERIES**

PAGE : 4/6

**6.2 MECHANICAL PERFORMANCE**

Test Description		Procedure		Requirement
6-2-1	Insertion & Withdrawal Force	Insert and withdraw connectors at the speed rate of $25 \pm 3\text{mm/minute}$ .		Refer to section 7
6-2-2	Crimping Pull Out Force	Fix the crimped terminal, apply axial pull out force on the wire at the speed rate of $25 \pm 3\text{mm/minute}$ . (Based upon JIS C5402 6.8)	AWG #24	30N/3.0kgf Min.
			AWG #26	20N/2.0kgf Min.
			AWG #28	10N/1.0kgf Min.
6-2-3	Locking Strength	A socket housing and a header shall be mated. A load shall be applied between them. The load to come them off each other shall be measured. Testing speed: $25 \pm 3\text{mm/minute}$ .		2x5P~2x6P: 1.5kgf Min. 2x7P~2x20P: 2.5kgf Min.
6-2-4	Terminal/Housing Retention Force	Apply axial pull out force at the speed rate of $25 \pm 3\text{mm/minute}$ on the terminal assembled in the housing.		1.0kgf Min.
6-2-5	Header Terminal Retention Force	Apply axial push force at the speed rate of $25 \pm 3\text{mm/minute}$ .		A1501WVE: 2x5P~2x15P: 0.3kgf Min. 2x16P~2x20P: 0.15kgf Min. A1501WRE: 0.15kgf Min.
6-2-6	Durability	When mated up to 30 cycles repeatedly by the rate of 10 cycles per minute.	Contact Resistance	60mΩ Max.
6-2-7	Vibration	Amplitude: 1.52mm P-P Sweep time: 10-55-10 Hz in 1 minute Duration: 2 hours in each X.Y.Z. axes (Based upon JIS C 60068-2-6/MIL-STD-202 Method 201)	Appearance	No Damage
			Contact Resistance	60mΩ Max.
			Discontinuity	1μsec. Max.

## PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1501-E SERIES

PAGE : 5/6

## 6.3 ENVIRONMENTAL PERFORMANCE AND OTHERS

Test Description		Procedure		Requirement
6-3-1	Temperature Rise	Carrying rated current load. (Based upon UL 498)	Temperature Rise	30°C Max.
6-3-2	Heat Resistance	85 ± 2°C, 250 hours (Based upon JIS C0021/MIL-STD-202 Method 108A Cond. A)	Appearance	No Damage
			Contact Resistance	60mΩ Max.
6-3-3	Humidity	Temperature: 40 ± 2°C Relative Humidity: 90 ~ 95% Duration: 240 hours (Based upon JIS C0022/MIL-STD-202 Method 103B Cond. B)	Appearance	No Damage
			Contact Resistance	60mΩ Max.
			Insulation Resistance	300MΩ Min.
			Dielectric Withstanding Voltage	Must meet 6-1-3
6-3-4	Temperature Cycling	25 cycles of: a) - 55°C 30 minutes b) +85°C 30 minutes (Based upon MIL-STD-202 Method 107 Cond. A-1)	Appearance	No Damage
			Contact Resistance	60mΩ Max.
6-3-5	Salt Spray	24 hours exposure to a salt spray from the 5 % solution at 35 ± 2°C. (Based upon JIS C0023/MIL-STD-202 Method 101D Cond. B)	Appearance	No Damage
			Contact Resistance	60mΩ Max.
6-3-6	Hydrogen Sulfide Gas	Concentration: 3 ± 1ppm. Temperature: 40 ± 2°C Relative Humidity: 80±5% 96 hours	Appearance	No Damage
			Contact Resistance	60mΩ Max.
6-3-7	NH <sub>3</sub> Gas	40 minutes exposure to NH <sub>3</sub> gas evaporating from 28% Ammonia solution.	Appearance	No Damage
			Contact Resistance	60mΩ Max.
6-3-8	Solderability	Soldering Time: 3~5 sec. Solder Temperature: 245 ± 5°C	Solder Wetting	95% of immersed area must show no voids, pin holes
6-3-9	Resistance to Soldering Heat	<u>Normal materials</u> Soldering Time:3~5 sec. Solder Temperature: 250± 5°C <u>High temperature resistant materials</u> Soldering Time:3~5 sec. Solder Temperature: 260 ± 5°C	Appearance	No Damage



PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1501-E SERIES

PAGE : 6/6

7. INSERTION AND WITHDRAWAL FORCE

unit:N

Number of Circuits (W-B)	Insertion (Max.)	Withdrawal (Min.)	
	1 th	1 th	30 th
2x5P	30	1.5	1.5
2x6P	33	2.0	2.0
2x7P	36	2.5	2.5
2x8P	39	3.0	3.0
2x9P	42	3.5	3.5
2x10P	45	4.0	4.0
2x11P	48	4.5	4.5
2x12P	51	5.0	5.0
2x13P	54	5.5	5.5
2x14P	57	6.0	6.0
2x15P	60	6.5	6.5
2x16P	63	7.0	7.0
2x17P	66	7.5	7.5
2x18P	69	8.0	8.0
2x19P	72	8.5	8.5
2x20P	75	9.0	9.0