



PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1502 SERIES

PAGE : 1/7

Index

1. Scope
2. Part name & part numbers
3. Construction. dimensions. material & surface finish
4. Ratings & applicable wires
5. Conditions
6. Performance
 - 6.1 Electrical performance
 - 6.2 Mechanical performance
 - 6.3 Environmental performance and others
7. Insertion and Withdrawal Force

			APPROVED	CHECKED	WRITTEN
			BY	BY	BY
			Jack Yin	Diankui Wan	Xi Chen
A0	NEW RELEASE	2022/12/29			
REV.	DESCRIPTION	DATE	DOCUMENT NO: PS-A1502-001		

PRODUCT SPECIFICATION
PRODUCT SERIES NAME: A1502 SERIES

PAGE : 2/7

1.SCOPE:

This specification covers the requirements for product performance of 1.50 mm pitch wire to wire or wire to board connector series.

2.PART NAME & PART NUMBERS

Part name	Part number
Housing	A1502H/HB
Terminal	A1502-T
Wafer	A1502WV/WV-S/WVA/WVB WR/WR-S/WRA/WRB

3. CONSTRUCTION. DIMENSIONS . MATERIAL & SURFACE FINISH

Construction and dimensions shall be in accordance with the referenced drawings. Material and surface finish shall be as specified below.

Part name		Material	Surface finish
Housing		Nylon 66	UL94V-0
Terminal		Phosphor bronze	Tin over Nickel/Gold over Nickel
Wafer	Post	Brass	Tin over Nickel/Gold over Nickel
	Body	Nylon 66/LCP	UL94V-0

4. RATINGS & APPLICABLE WIRES

Item	Standard				
Rated Voltage (Max.)	250V AC DC				Insulation O.D. 1.10mm Max.
Rated Current (Max.) and Applicable Wires	No.of circuits	Wire size (AWG)			
		#24	#26	#28	
	2-circuits	3.5	3.0	3.0	
	8-circuits	2.5	2.0	2.0	
	15-circuits	2.5	2.0	1.5	
Ambient Temperature Range		-40℃~105℃*			

Note: Do not branch in parallel current which exceeds the rated current

*: Including terminal temperature rise

PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1502 SERIES

PAGE : 3/7

5. CONDITIONS:

The conditions shall be in accordance with the referenced data of next table.

Number	Item	Requirement
(1)	Bend up	3°Max.
	Bend down	3°Max.
	Twisting	3°Max.
	Rolling	4°Max.
(2)	Bell mouth (flare)	0.05-0.30 mm
(3)	Cut-off tab length	0.15 mm Max.
(4)	Extruded wire length	0-0.50 mm
(5)	Seam	Seam shall not be opened and no wire allowed out of crimping area
(6)	Wire strip length	1.05-1.54 mm ref.

After crimping, the crimped areas [(5)、(6)] should be as follows.

Wire Size (AWG)	Terminal Part Number	Conductor(mm)		Insulation(mm)		Crimp Strength (kgf)
		Crimp Width	Crimp Height	Crimp Width	Crimp Height	
# 24	A1502-T	1.00	0.56~0.60	1.10	1.45	3.00(Min.)
# 26			0.52~0.58		1.40	2.00(Min.)
# 28			0.50~0.55		1.26	1.00(Min.)

The crimp width at the conductor part & crimp height at the insulation part is a reference value, so adjust it according to a wire to be used.

PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1502 SERIES

PAGE : 4/7

6. PERFORMANCE

6.1 ELECTRICAL PERFORMANCE

Test Description		Procedure	Requirement
6-1-1	Contact Resistance	Mate connectors, measure by dry circuit, 20mV Max. 10mA.	20mΩ Max.
6-1-2	Insulation Resistance	Mate connectors, apply 500V DC between adjacent terminal or ground.	1000MΩ Min.
6-1-3	Dielectric Withstanding Voltage	Mate connectors, apply 500V AC (rms) for 1 minute between adjacent terminal or ground.	No Breakdown and Flashover

6.2 MECHANICAL PERFORMANCE

Test Description		Procedure		Requirement
6-2-1	Insertion & Withdrawal Force	Insert and withdraw connectors at the speed rate of 25 ± 3 mm/minute.		Refer to section 7
6-2-2	Crimping Pull Out Force	Fix the crimped terminal, apply axial pull out force on the wire at the speed rate of 25 ± 3 mm/minute.	AWG #24	3.0kgf Min.
			AWG #26	2.0kgf Min.
			AWG #28	1.0kgf Min.
6-2-3	Crimp Terminal Insertion Force	Insert the crimped terminal into the housing. Testing speed: 25 ± 3 mm/minute.		1.0kgf Max.
6-2-4	Terminal/Housing Retention Force	Apply axial pull out force at the speed rate of 25 ± 3 mm/minute on the terminal assembled in the housing.		1.0kgf Min.
6-2-5	Header Terminal Retention Force	Apply axial push force at the speed rate of 25 ± 3 mm/minute.	After reflow	1.0kgf Min.(tin) 0.7kgf Min.(gold)
6-2-6	Durability	When mated up to 10 cycles repeatedly.	Contact Resistance	40mΩ Max.



PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1502 SERIES

PAGE : 5/7

6-2-7	Vibration	Amplitude: 1.52mm P-P Sweep time: 10-55-10 Hz in 1 minute Duration: 2 hours in each X.Y.Z. axes	Appearance	No Damage
			Contact Resistance	40mΩ Max.
			Discontinuity	1μsec. Max.
6-2-8	Mechanical Shock	Mate connectors and subject to the following shock conditions. 3 shocks shall be applied 6 directions along 3 mutually perpendicular axes (±x, ±y, ±z, each), passing DC 1 mA current during the test. (Total of 18 shocks) Test pulse : Half Sine Peak value : 490 m/s ² (50 G) Duration : 11 ms	Appearance	No Damage
			Contact Resistance	40mΩ Max.
			Discontinuity	1μsec. Max.

PRODUCT SPECIFICATION
PRODUCT SERIES NAME: A1502 SERIES
PAGE : 6/7
6.3 ENVIRONMENTAL PERFORMANCE AND OTHERS

Test Description		Procedure		Requirement
6-3-1	Temperature Rise	Carrying rated current load.	Temperature Rise	30°C Max.
6-3-2	Heat Resistance	105 ± 2°C, 168 hours	Appearance	No Damage
			Contact Resistance	40mΩ Max.
6-3-3	Cold Resistance	-55 ± 2°C, 96 hours	Appearance	No Damage
			Contact Resistance	40mΩ Max.
6-3-4	Humidity	Temperature: 85 ± 2°C Relative Humidity: 85 ± 3% Duration: 168 hours	Appearance	No Damage
			Contact Resistance	40mΩ Max.
			Insulation Resistance	1000MΩ Min.
			Dielectric Withstanding Voltage	No Breakdown and Flashover
6-3-5	Salt Spray	24 hours exposure to a salt spray from the 5 % solution at 35 ± 2°C.	Appearance	No Damage
			Contact Resistance	40mΩ Max.
6-3-6	Solderability	Soldering Time: 5± 0.5 sec. Solder Temperature: 245 ± 5°C	Solder Wetting	95% of immersed area must show no voids, pin holes
6-3-7	Resistance to Soldering Heat	<u>Normal materials</u> Soldering Time:3~5 sec. Solder Temperature: 250± 5°C <u>High temperature resistant materials</u> Soldering Time:3~5 sec. Solder Temperature: 260 ± 5°C	Appearance	No Damage



PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A1502 SERIES

PAGE : 7/7

7. INSERTION AND WITHDRAWAL FORCE

PREPLATED TIN

unit: kgf

Number of Circuits	Insertion (Max.)	Withdrawal (Min.)	
	1 th	1 th	10 th
2P	2.5	1.0	0.6
3P	3.0	1.0	0.6
4P	3.5	1.0	0.6
5P	4.0	1.0	0.8
6P	4.5	1.0	0.8
7P	5.0	1.0	0.8
8P	5.5	1.5	1.0
9P	5.5	1.5	1.0
10P	6.0	1.5	1.0
11P	6.0	1.5	1.0
12P	6.5	1.5	1.0
13P	6.5	1.5	1.0
14P	7.0	1.5	1.0
15P	7.0	1.5	1.0