



PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A2001 SERIES

PAGE : 1/6

Index

1. Scope
2. Part name & part numbers
3. Construction. dimensions. material & surface finish
4. Ratings & applicable wires
5. Conditions
6. Performance
 - 6.1 Electrical performance
 - 6.2 Mechanical performance
 - 6.3 Environmental performance and others
7. Insertion and Withdrawal Force

			APPROVED	CHECKED	WRITTEN
			BY	BY	BY
A2	REVISE	2021.08.27	<i>Jack Yin</i>	<i>Diankui Wan</i>	<i>Dengchun Yi</i>
A1	REVISE	2020.11.13			
A0	NEW RELEASE	2010.08.20			
REV.	DESCRIPTION	DATE	DOCUMENT NO: PS-A2001-002		



PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A2001 SERIES

PAGE : 2/6

1.SCOPE:

This specification covers the requirements for product performance of 2.00 mm pitch wire to board or wire to wire connector series.

2.PART NAME & PART NUMBERS

Part name	Part number
Housing	A2001H A2001HM
Terminal	A2001-T(-L) A2001M-T
Wafer	A2001WV A2001WR A2001WV-H A2001WV-F-H
	A2001WV-S A2001WR-S

3. CONSTRUCTION. DIMENSIONS . MATERIAL & SURFACE FINISH

Construction and dimensions shall be in accordance with the referenced drawings.

Material and surface finish shall be as specified below.

Part name	Material		Surface finish
Housing	Nylon 66		UL94V-0
Terminal	Phosphor bronze		Tin over Nickel/Gold over Nickel
Wafer	Post	Brass	Tin over Nickel/Gold over Nickel
	Body	PA 66/PA 46/PA 9T/LCP	UL94V-0

4. RATINGS & APPLICABLE WIRES

Item	Standard		
Rated Voltage (Max.)	100V AC DC		Insulation O.D. 0.80~1.50mm 0.50~0.90mm
Rated Current (Max.) and Applicable Wires	AWG #24	2.0A AC DC	
	AWG #26	1.5A AC DC	
	AWG #28	1.0A AC DC	
	AWG #30	1.0A AC DC	
	AWG #32	0.8A AC DC	
Ambient Temperature Range	-40℃~105℃*		

*: Including terminal temperature rise

PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A2001 SERIES

PAGE : 3/6

5. CONDITIONS:

The conditions shall be in accordance with the referenced data of next table.

Number	Item	Requirement
(1)	Bend up	6°Max.
	Bend down	6°Max.
	Twisting	5°Max.
	Rolling	7°Max.
(2)	Bell mouth (flare)	0.1-0.3 mm
(3)	Cut-off tab length	0.5 mm Max.
(4)	Extruded wire length	0.3-0.6 mm
(5)	Seam	Seam shall not be opened and no wire allowed out of crimping area
(6)	Wire strip length	1.9-2.5 mm ref.
(7)	Lance height	0.5 mm ref.

After crimping, the crimped areas [(5)、(6)] should be as follows.

Wire Size (AWG)	Terminal Part Number	Conductor(mm)		Insulation(mm)		Crimp Strength (kgf)
		Crimp Width	Crimp Height	Crimp Width	Crimp Height	
# 24	A2001-T A2001-T-L	1.20	0.62~0.67	1.50	1.70	3.00(Min.)
# 26			0.57~0.62		1.60	2.00(Min.)
# 28			0.55~0.60		1.50	1.50(Min.)
# 30			0.52~0.55		1.50	0.80(Min.)
# 32			0.47~0.52		1.10	0.30(Min.)

The crimp width at the conductor part & crimp height at the insulation part is a reference value, so adjust it according to a wire to be used.

6. PERFORMANCE

6.1 ELECTRICAL PERFORMANCE

Test Description		Procedure	Requirement
6-1-1	Contact Resistance	Mate connectors, measure by dry circuit, 20mV Max. 10mA. (Based upon JIS C5402 5.4)	10mΩ Max.
6-1-2	Insulation Resistance	Mate connectors, apply 250V DC between adjacent terminal or ground. (Based upon JIS C5402 5.2/MIL-STD-202 Method 302 Cond. B)	1000MΩ Min.
6-1-3	Dielectric Withstanding Voltage	Mate connectors, apply 800V AC (rms) for 1 minute between adjacent terminal or ground. (Based upon JIS C5402 5.1/MIL-STD-202 Method 301)	No Breakdown

PRODUCT SPECIFICATION
PRODUCT SERIES NAME: A2001 SERIES

PAGE : 4/6

6-1-4	Contact Resistance on Crimped Portion	Crimp the applicable wire to the terminal, measured by dry circuit, 20mV Max, 10 mA Max.	5mΩ Max.
-------	---------------------------------------	--	----------

6.2 MECHANICAL PERFORMANCE

Test Description		Procedure		Requirement
6-2-1	Insertion & Withdrawal Force	Insert and withdraw connectors at the speed rate of 25 ± 3 mm/minute.		Refer to section 7
6-2-2	Crimping Pull Out Force	Fix the crimped terminal, apply axial pull out force on the wire at the speed rate of 25 ± 3 mm/minute. (Based upon JIS C5402 6.8)	AWG #24	3.0kgf Min.
			AWG #26	2.0kgf Min.
			AWG #28	1.5kgf Min.
			AWG #30	0.8kgf Min.
			AWG #32	0.3kgf Min.
6-2-3	Terminal/Housing Retention Force	Apply axial pull out force at the speed rate of 25 ± 3 mm/minute on the terminal assembled in the housing.		1.5kgf Min.
6-2-4	Header Terminal Retention Force	Apply axial push force at the speed rate of 25 ± 3 mm/minute.		1.0kgf Min.
6-2-5	Durability	When mated up to 50 cycles repeatedly by the rate of 10 cycles per minute.	Contact Resistance	20mΩ Max.
6-2-6	Vibration	Amplitude: 1.52mm P-P Sweep time: 10-55-10 Hz in 1 minute Duration: 2 hours in each X.Y.Z. axes (Based upon MIL-STD-202 Method 201A)	Appearance	No Damage
			Contact Resistance	20mΩ Max.
			Discontinuity	1μsec. Max.

PRODUCT SPECIFICATION
PRODUCT SERIES NAME: A2001 SERIES

PAGE : 5/6

6.3 ENVIRONMENTAL PERFORMANCE AND OTHERS

Test Description		Procedure		Requirement
6-3-1	Temperature Rise	Carrying rated current load. (Based upon UL 498)	Temperature Rise	30°C Max.
6-3-2	Heat Resistance	85 ± 2°C, 250 hours (Based upon JIS C0021/MIL-STD-202 Method 108A Cond. A)	Appearance	No Damage
			Contact Resistance	20mΩ Max.
6-3-3	Humidity	Temperature: 40 ± 2°C Relative Humidity: 90 ~ 95% Duration: 96 hours (Based upon JIS C0022/MIL-STD-202 Method 103B Cond. B)	Appearance	No Damage
			Contact Resistance	20mΩ Max.
			Insulation Resistance	500MΩ Min.
			Dielectric Withstanding Voltage	Must meet 6-1-3
6-3-4	Temperature Cycling	25 cycles of: a) - 55°C 30 minutes b) +85°C 30 minutes (Based upon JIS C0025)	Appearance	No Damage
			Contact Resistance	20mΩ Max.
6-3-5	Salt Spray	24 hours exposure to a salt spray from the 5 % solution at 35 ± 2°C. (Based upon JIS C0023/MIL-STD-202 Method 101D Cond. B)	Appearance	No Damage
			Contact Resistance	20mΩ Max.
6-3-6	Hydrogen Sulfide Gas	Concentration: 3 ± 1ppm. Temperature: 40 ± 2°C Relative Humidity: 80±5% 96 hours	Appearance	No Damage
			Contact Resistance	20mΩ Max.
6-3-7	Solderability	Soldering Time: 3~5 sec. Solder Temperature: 245 ± 5°C	Solder Wetting	95% of immersed area must show no voids, pin holes
6-3-8	Resistance to Soldering Heat	<u>Normal materials</u> Soldering Time:3~5 sec. Solder Temperature: 250± 5°C <u>High temperature resistant materials</u> Soldering Time:3~5 sec. Solder Temperature: 260 ± 5°C <u>Iron soldering</u> Soldering Time:3 sec. Solder Temperature: 340 ± 5°C	Appearance	No Damage



PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A2001 SERIES

PAGE : 6/6

7. INSERTION AND WITHDRAWAL FORCE

unit:N

Number of Circuits (W-B)	Insertion (Max.)	Withdrawal (Min.)	
		1 th	50 th
2P	24.5	7.8	5.9
3P	29.4	7.8	5.9
4P	34.3	9.8	7.8
5P	39.2	9.8	7.8
6P	44.1	11.8	9.8
7P	49.0	11.8	9.8
8P	53.9	13.7	11.8
9P	58.8	13.7	11.8
10P	63.7	15.7	13.7
11P	68.6	15.7	13.7
12P	73.5	17.7	15.7
13P	78.5	19.6	17.7
14P	78.5	19.6	17.7
15P	78.5	19.6	17.7
16P	93.1	25.5	21.6