



PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A2011 SERIES

PAGE : 1/6

Index

1. Scope
2. Part name & part numbers
3. Construction. dimensions. material & surface finish
4. Ratings & applicable wires
5. Conditions
6. Performance
 - 6.1 Electrical performance
 - 6.2 Mechanical performance
 - 6.3 Environmental performance and others
7. Insertion and Withdrawal Force

			APPROVED	CHECKED	WRITTEN
			BY	BY	BY
			Jack Yin	Lailin	Diankui Wan
A1	REVISE	2020.05.13			
A0	NEW RELEASE	2013.08.06			
REV.	DESCRIPTION	DATE	DOCUMENT NO: PS-A2011-004		

PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A2011 SERIES

PAGE : 2/6

1.SCOPE:

This specification covers the requirements for product performance of 2.00 mm pitch wire to board or wire to wire connector series.

2.PART NAME & PART NUMBERS

Part name	Part number
Housing	A2011H A2011HM
Terminal	A2011-T A2011M-T
Wafer	A2011WV A2011WR

3. CONSTRUCTION. DIMENSIONS . MATERIAL & SURFACE FINISH

Construction and dimensions shall be in accordance with the referenced drawings.

Material and surface finish shall be as specified below.

Part name		Material	Surface finish
Housing		Nylon 66	UL94V-0
Terminal		Phosphor bronze	Tin over Nickel/Gold over Nickel
Wafer	Post	Brass	Tin over Nickel/Gold over Nickel
	Body	Nylon 66/Nylon 6T	UL94V-0

4. RATINGS & APPLICABLE WIRES

Item	Standard		
Rated Voltage (Max.)	250V AC DC		Insulation O.D. 0.90mm~1.45mm
Rated Current (Max.) and Applicable Wires	AWG #22	3.0A AC DC	
	AWG #24	2.5A AC DC	
	AWG #26	2.5A AC DC	
	AWG #28	1.0A AC DC	
Ambient Temperature Range	-40℃~105℃*		

*: Including terminal temperature rise

PRODUCT SPECIFICATION
PRODUCT SERIES NAME: A2011 SERIES

PAGE : 3/6

5. CONDITIONS:

The conditions shall be in accordance with the referenced data of next table.

Number	Item	Requirement
(1)	Bend up	3°Max.
	Bend down	3°Max.
	Twisting	3°Max.
	Rolling	6°Max.
(2)	Bell mouth (flare)	0.05-0.4 mm
(3)	Cut-off tab length	0.3 mm Max.
(4)	Extruded wire length	0.1-0.7 mm
(5)	Seam	Seam shall not be opened and no wire allowed out of crimping area
(6)	Wire strip length	1.6-2.0 mm ref.
(7)	Lance height	0.3 mm ref.

After crimping, the crimped areas [(5)、(6)] should be as follows.

Wire Size (AWG)	Terminal Part Number	Conductor(mm)		Insulation(mm)		Crimp Strength (kgf)
		Crimp Width	Crimp Height	Crimp Width	Crimp Height	
# 22	A2011-T A2011M-T	1.30±0.10	0.70~0.75	1.60(Max.)	1.80(max)	4.00(min)
# 24			0.65~0.70		1.70(max)	3.00(min)
# 26			0.60~0.65		1.60(max)	2.00(min)
# 28			0.55~0.60		1.50(max)	1.00(min)

6. PERFORMANCE
6.1 ELECTRICAL PERFORMANCE

Test Description		Procedure	Requirement
6-1-1	Contact Resistance	Mate connectors, measure by dry circuit, 20mV Max. 10mA. (Based upon JIS C5402 5.4)	20mΩ Max.
6-1-2	Insulation Resistance	Mate connectors, apply 500V DC between adjacent terminal or ground. (Based upon JIS C5402 5.2/MIL-STD-202 Method 302 Cond. B)	1000MΩ Min.
6-1-3	Dielectric Withstanding Voltage	Mate connectors, apply 1000V AC (rms) for 1 minute between adjacent terminal or ground. (Based upon JIS C5402 5.1/MIL-STD-202 Method 301)	No Breakdown

PRODUCT SPECIFICATION
PRODUCT SERIES NAME: A2011 SERIES

PAGE : 4/6

6.2 MECHANICAL PERFORMANCE

Test Description		Procedure		Requirement
6-2-1	Insertion & Withdrawal Force	Insert and withdraw connectors at the speed rate of 25 ± 3 mm/minute.		Refer to section 7
6-2-2	Crimping Pull Out Force	Fix the crimped terminal, apply axial pull out force on the wire at the speed rate of 25 ± 3 mm/minute. (Based upon JIS C5402 6.8)	AWG #22	39.2N/4.0kgf Min.
			AWG #24	29.4N/3.0kgf Min.
			AWG #26	19.6N/2.0kgf Min.
			AWG #28	9.8N/1.0kgf Min.
6-2-3	Crimp Terminal Insertion Force	Insert the crimped terminal into the housing.		1.0kgf Max.
6-2-4	Terminal/Housing Retention Force	Apply axial pull out force at the speed rate of 25 ± 3 mm/minute on the terminal assembled in the housing.		1.0kgf Min.
6-2-5	Header Terminal Retention Force	Apply axial push force at the speed rate of 25 ± 3 mm/minute.		1.0kgf Min.
6-2-6	Housing Lock Strength (Positive Lock)	Mate connectors and apply axial pull out force at the speed rate of 25 ± 3 mm/minute.		3.0kgf Min.
6-2-7	Durability	When mated up to 30 cycles repeatedly by the rate of 10 cycles per minute.	Contact Resistance	40mΩ Max.
6-2-8	Vibration	Amplitude: 1.52mm P-P Sweep time: 10-55-10 Hz in 1 minute Duration: 2 hours in each X.Y.Z. axes (Based upon JIS C 60068-2-6/MIL-STD-202 Method 201)	Appearance	No Damage
			Contact Resistance	40mΩ Max.
			Discontinuity	1μsec. Max.
6-2-9	Physical Shock	490m/s ² {50G}, 3 strokes in each X.Y.Z. axes. (Based upon JIS C60068-2-27/MIL-STD-202 Method 213 B Cond. A)	Appearance	No Damage
			Contact Resistance	40mΩ Max.
			Discontinuity	1μsec. Max.

PRODUCT SPECIFICATION
PRODUCT SERIES NAME: A2011 SERIES

PAGE : 5/6

6.3 ENVIRONMENTAL PERFORMANCE AND OTHERS

Test Description		Procedure		Requirement
6-3-1	Temperature Rise	Carrying rated current load. (Based upon UL 498)	Temperature Rise	30°C Max.
6-3-2	Heat Resistance	105 ± 2°C, 96 hours (Based upon JIS C0021/MIL-STD-202 Method 108A Cond. A)	Appearance	No Damage
			Contact Resistance	40mΩ Max.
6-3-3	Cold Resistance	-40 ± 3°C, 96 hours (Based upon JIS C0020)	Appearance	No Damage
			Contact Resistance	40mΩ Max.
6-3-4	Humidity	Temperature: 40 ± 2°C Relative Humidity: 90 ~ 95% Duration: 96 hours (Based upon JIS C0022/MIL-STD-202 Method 103B Cond. B)	Appearance	No Damage
			Contact Resistance	40mΩ Max.
			Insulation Resistance	100MΩ Min.
			Dielectric Withstanding Voltage	Must meet 6-1-3
6-3-5	Temperature Cycling	25 cycles of: a) - 55°C 30 minutes b) +105°C 30 minutes (Based upon JIS C60068-2-14)	Appearance	No Damage
			Contact Resistance	40mΩ Max.
6-3-6	Salt Spray	24 hours exposure to a salt spray from the 5 % solution at 35 ± 2°C. (Based upon JIS C0023/MIL-STD-202 Method 101D Cond. B)	Appearance	No Damage
			Contact Resistance	40mΩ Max.
6-3-7	Solderability	Soldering Time: 3~5 sec. Solder Temperature: 240 ± 5°C	Solder Wetting	95% of immersed area must show no voids, pin holes
6-3-8	Resistance to Soldering Heat	<u>Normal materials</u> Soldering Time:3~5 sec. Solder Temperature: 250 ± 5°C <u>High temperature resistant materials</u> Soldering Time:3~5 sec. Solder Temperature: 260 ± 5°C	Appearance	No Damage

PRODUCT SPECIFICATION

PRODUCT SERIES NAME: A2011 SERIES

PAGE : 6/6

7. INSERTION AND WITHDRAWAL FORCE

unit: kgf

Number of Circuits	Insertion (Max.)	Withdrawal (Min.)
2	3.00	0.50
3	3.50	0.70
4	4.00	0.90
5	4.50	1.10
6	5.00	1.30
7	5.50	1.50
8	6.00	1.70
9	6.50	1.90
10	7.00	2.10
11	7.50	2.30
12	8.00	2.50
13	8.50	2.70
14	9.00	2.90
15	9.50	3.10