



SPECIFICATIONS:

Current Rating: 1A AC,DC
Voltage Rating: 30V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 30mΩ Max.
Insulation Resistance: 100MΩ Min.
Withstanding Voltage: 200V AC/minute
Material: Nylon 9T,UL94V-0(Black)

Ordering Information & Dimensions

Part NO.	Dimensions(mm)	
	A	B
A0801HA-2P	0.80	3.50
A0801HA-3P	1.60	4.30
A0801HA-4P	2.40	5.10
A0801HA-5P	3.20	5.90
A0801HA-6P	4.00	6.70
A0801HA-7P	4.80	7.50
A0801HA-8P	5.60	8.30
A0801HA-9P	6.40	9.10
A0801HA-10P	7.20	9.90
A0801HA-11P	8.00	10.70
A0801HA-12P	8.80	11.50
A0801HA-13P	9.60	12.30
A0801HA-14P	10.40	13.10
A0801HA-15P	11.20	13.90
A0801HA-16P	12.00	14.70
A0801HA-17P	12.80	15.50
A0801HA-18P	13.60	16.30
A0801HA-19P	14.40	17.10
A0801HA-20P	15.20	17.90

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet	TITLE 0.80mm PITCH HOUSING	
mm	8:1	1 of 1		
DRWN	CHK'D	APPR		
Dengchun Yi	Diankui Wan	Jack Yin	DRAWING NO. A0801HA-XP	
General Tolerances		THIRD ANGLE PROJECTION 		
x,x±0.25				
x,x,x±0.20				
x,x,x,x±0.15				
ANGLES ±1°		REV A1		