



SPECIFICATIONS:

Current Rating: 1A AC,DC
Voltage Rating: 200V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 40mΩ Max.
Insulation Resistance: 100MΩ Min.
Withstanding Voltage: 500V AC/minute
Pin Material: Phosphor Bronze/Gold over Nickel
Solder Tabs: Phosphor Bronze/Gold over Nickel
Material: Nylon 6T,UL94V-0(Beige)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2P	1.25	6.10	4.01	11P	12.50	17.35	15.26
3P	2.50	7.35	5.26	12P	13.75	18.60	16.51
4P	3.75	8.60	6.51	13P	15.00	19.85	17.76
5P	5.00	9.85	7.76	14P	16.25	21.10	19.01
6P	6.25	11.10	9.01	15P	17.50	22.35	20.26
7P	7.50	12.33	10.26	20P	23.75	28.60	26.51
8P	8.75	13.60	11.51	25P	30.00	34.85	32.76
10P	11.25	16.10	14.01	30P	36.25	41.10	39.01

CJTconn			CHANGJIANG CONNECTORS CO.,LTD.	
Unit	Scale	Sheet	TITLE	
mm	5:1	1 of 1		
DRAWN	CHKD	APPR	1.25mm PITCH RIGHT-ANGLE WAFER - SMT TYPE ULTRA LOW PROFILE	
Chengbiao Ye	Djankui Wan	Jack Yin		
9	General Tolerances	THIRD ANGLE PROJECTION	DRAWING NO.	
2	x.xx±0.25 x.xxx±0.20 x.xxxx±0.15 ANGLES ±1°			
0			REV A2	
			A1256WR-S-XP	

A2	CHANGE THE DRAWING	2022.12.19
A1	CHANGE THE DRAWING	2021.08.02
A0	NEW RELEASE	2005.05.10
REV	DESCRIPTION	DATE

P.C.B LAYOUT

