





P.C.B LAYOUT
TOLERANCE:±0.05

Ordering Information:
A2001WRA-XP-P-LCP - ** - ***
1 2 3

- 1.Part No.
2.Finish:
(Blank): Tin over Nickel
G:Gold over Nickel (Au:1u")
G3: Gold over Nickel(Au:3u")
G15: Gold over Nickel(Au:15u",Mating Area)
G30: Gold over Nickel(Au:30u",Mating Area)
3.Packing:
(Blank): Bag
RE: Tape & Reel

SPECIFICATIONS:
Current Rating: 2A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 20mΩ Max.
Insulation Resistance: 1000MΩ Min.
Withstanding Voltage: 1000V AC/minute
Pin Material: Brass
Material: LCP,UL94V-0(Beige)

Ordering Information & Dimensions

Part NO.	Dimensions(mm)		
	A	B	C
A2001WRA-2P-P-LCP	2.00	6.00	4.90
A2001WRA-3P-P-LCP	4.00	8.00	6.90
A2001WRA-4P-P-LCP	6.00	10.00	8.90
A2001WRA-5P-P-LCP	8.00	12.00	10.90
A2001WRA-6P-P-LCP	10.00	14.00	12.90
A2001WRA-7P-P-LCP	12.00	16.00	14.90
A2001WRA-8P-P-LCP	14.00	18.00	16.90
A2001WRA-9P-P-LCP	16.00	20.00	18.90
A2001WRA-10P-P-LCP	18.00	22.00	20.90
A2001WRA-11P-P-LCP	20.00	24.00	22.90
A2001WRA-12P-P-LCP	22.00	26.00	24.90
A2001WRA-13P-P-LCP	24.00	28.00	26.90
A2001WRA-14P-P-LCP	26.00	30.00	28.90
A2001WRA-15P-P-LCP	28.00	32.00	30.90
A2001WRA-16P-P-LCP	30.00	34.00	32.90

CJTconn				CHANGJIANG CONNECTORS CO.,LTD.	
Unit	Scale	Sheet	TITLE		
mm	5:1	1 of 1	2.00mm PITCH RIGHT-ANGLE WAFER		
DRWN	CHK'D	APPR			
Wenmin Luo	Diankui Wan	Jack Yin			
General Tolerances		THIRD ANGLE PROJECTION		DRAWING NO.	
x.xx±0.25 x.xxx±0.20 x.xxxx±0.15 ANGLES ±1°					
				REV A0	
				A2001WRA-XP-P-LCP	