








Ordering Information:
A2005WR-XP- *** _ * _ ***
1 2 3 4

- 1.Part No.
- 2.Size(H):
(Blank):2.00mm
H15:1.50mm
H10:1.00mm
- 3.Material:
(Blank):PBT,UL94V-0
6T:Nylon 6T,UL94V-0
GWT:Nylon 6T,UL94V-0 GWT 750℃
- 4.Finish:
(Blank):Gold over Nickel
T: Tin over Nickel



P.C.B LAYOUT



SPECIFICATIONS:

Current Rating: 2A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -40℃ ~ +105℃
Contact Resistance: 20mΩ Max.
Insulation Resistance: 1000MΩ Min.
Withstanding Voltage: 500V AC/minute
Pin Material: Brass/Gold over Nickel
Material: PBT,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dim(mm)		Circuits	Dim(mm)		Circuits	Dim(mm)	
	A	B		A	B		A	B
2P	2.00	4.00	15P	28.00	30.00	28P	54.00	56.00
3P	4.00	6.00	16P	30.00	32.00	29P	56.00	58.00
4P	6.00	8.00	17P	32.00	34.00	30P	58.00	60.00
5P	8.00	10.00	18P	34.00	36.00	31P	60.00	62.00
6P	10.00	12.00	19P	36.00	38.00	32P	62.00	64.00
7P	12.00	14.00	20P	38.00	40.00	33P	64.00	66.00
8P	14.00	16.00	21P	40.00	42.00	34P	66.00	68.00
9P	16.00	18.00	22P	42.00	44.00	35P	68.00	70.00
10P	18.00	20.00	23P	44.00	46.00	36P	70.00	72.00
11P	20.00	22.00	24P	46.00	48.00	37P	72.00	74.00
12P	22.00	24.00	25P	48.00	50.00	38P	74.00	76.00
13P	24.00	26.00	26P	50.00	52.00	39P	76.00	78.00
14P	26.00	28.00	27P	52.00	54.00	40P	78.00	80.00

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit		Scale		Sheet		TITLE 2.00mm PITCH RIGHT ANGLE SINGLE ROW PIN HEADER		
mm		5:1		1 of 1				
DRWN		CHK'D		APPR				
Wenmin Luo		Diankui Wan		Jack Yin				
0	General Tolerances			THIRD ANGLE PROJECTION			DRAWING NO. A2005WR-XP-D090	REV A2
2	x.xx±0.25							
3	x.xxx±0.20							
	x.xxxx±0.15							
	ANGLES ±1°							

A2	CHANGE THE DRAWING	2021.12.20
A1	CHANGE THE DRAWING	2020.03.02
A0	NEW RELEASE	2011.05.13
REV	DESCRIPTION	DATE