









Ordering Information:

A2005WV-S-XP - * - * - * - *

- 1.Part No.
- 2.Style:
A:Type A
B:Type B
- 3.Size(H):
(blank):2.00mm
H15: 1.50mm
- 4.Material:
(Blank):Nylon 6T,UL94V-0
GWT:Nylon 6T,UL94V-0 GWT 750℃
- 5.Finish:
(Blank):Gold over Nickel
T:Tin over Nickel

SPECIFICATIONS:

Current Rating: 2A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -40℃ ~ +105℃
Contact Resistance: 20mΩ Max.
Insulation Resistance: 1000MΩ Min.
Withstanding Voltage: 500V AC/minute
Pin Material: Brass/Gold over Nickel
Material: Nylon 6T,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dim(mm)		Circuits	Dim(mm)		Circuits	Dim(mm)	
	A	B		A	B		A	B
2P	2.00	4.00	15P	28.00	30.00	28P	54.00	56.00
3P	4.00	6.00	16P	30.00	32.00	29P	56.00	58.00
4P	6.00	8.00	17P	32.00	34.00	30P	58.00	60.00
5P	8.00	10.00	18P	34.00	36.00	31P	60.00	62.00
6P	10.00	12.00	19P	36.00	38.00	32P	62.00	64.00
7P	12.00	14.00	20P	38.00	40.00	33P	64.00	66.00
8P	14.00	16.00	21P	40.00	42.00	34P	66.00	68.00
9P	16.00	18.00	22P	42.00	44.00	35P	68.00	70.00
10P	18.00	20.00	23P	44.00	46.00	36P	70.00	72.00
11P	20.00	22.00	24P	46.00	48.00	37P	72.00	74.00
12P	22.00	24.00	25P	48.00	50.00	38P	74.00	76.00
13P	24.00	26.00	26P	50.00	52.00	39P	76.00	78.00
14P	26.00	28.00	27P	52.00	54.00	40P	78.00	80.00

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit: mm
Scale: 4:1
Sheet: 1 of 1

Draw By: Diankui Wan
Approved: Jack Yin

Title: 2.00mm Pitch
180° Single Row Pin Header
- SMD Type

A2	CHANGE THE SIZE C & D	2020.05.09
A1	CHANGE THE DRAWING	2018.12.06
A0	NEW RELEASE	2017.11.08
REV	DESCRIPTION	DATE

General Tolerance	PROJECT
x.x±0.25 x.xx±0.20 x.xxx±0.15	

DRAW NO: A2005WV-S-XP
REV A2