






SPECIFICATIONS:

Current Rating: 3A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -40°C ~ +105°C
 Contact Resistance: 20mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: PBT,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2x2P	2.54	9.58	5.08	2x18P	43.18	50.22	45.72
2x3P	5.08	12.12	7.62	2x19P	45.72	52.76	48.26
2x4P	7.62	14.66	10.16	2x20P	48.26	55.30	50.80
2x5P	10.16	17.20	12.70	2x21P	50.80	57.84	53.34
2x6P	12.70	19.74	15.24	2x22P	53.34	60.38	55.88
2x7P	15.24	22.28	17.78	2x23P	55.88	62.92	58.42
2x8P	17.78	24.82	20.32	2x24P	58.42	65.46	60.96
2x9P	20.32	27.36	22.86	2x25P	60.96	68.00	63.50
2x10P	22.86	29.90	25.40	2x26P	63.50	70.54	66.04
2x11P	25.40	32.44	27.94	2x27P	66.04	73.08	68.58
2x12P	27.94	34.98	30.48	2x28P	68.58	75.62	71.12
2x13P	30.48	37.52	33.02	2x29P	71.12	78.16	73.66
2x14P	33.02	40.06	35.56	2x30P	73.66	80.70	76.20
2x15P	35.56	42.60	38.10	2x31P	76.20	83.24	78.74
2x16P	38.10	45.14	40.64	2x32P	78.74	85.78	81.28
2x17P	40.64	47.68	43.18				

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet	TITLE	
mm	3:1	1 of 1		
DRWN	CHK'D	APPR	2.54mm PITCH HOUSING	
Dengchun Yi	Dlankui Wan	Jack Yin		
General Tolerances		THIRD ANGLE PROJECTION	DRAWING NO.	REV A2
x.xx±0.25 x.xxx±0.20 x.xxxx±0.15 ANGLES ±1°				
			A2547HK-2xXP	

A2	CHANGE THE DRAWING	2020.10.24
A1	CHANGE THE SIZE	2018.11.05
A0	NEW RELEASE	2017.06.25
REV	DESCRIPTION	DATE