

SPECIFICATIONS:

Current Rating: 3A AC,DC
Voltage Rating: 300V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 5mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1100V AC/minute
Material: PBT30%GF,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	2.54	5.08	14P	33.02	35.56
3P	5.08	7.62	15P	35.56	38.10
4P	7.62	10.16	16P	38.10	40.64
5P	10.16	12.70	17P	40.64	43.18
6P	12.70	15.24	18P	43.18	45.72
7P	15.24	17.78	19P	45.72	48.26
8P	17.78	20.32	20P	48.26	50.80
9P	20.32	22.86	21P	50.80	53.34
10P	22.86	25.40	22P	53.34	55.88
11P	25.40	27.94	23P	55.88	58.42
12P	27.94	30.48	24P	58.42	60.96
13P	30.48	33.02	25P	60.96	63.50

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.


Unit	Scale	Sheet
mm	5:1	1 of 1

Draw BY:	Approved :
Diankui Wan	Jack Yin



General Tolerance

A1	CHANGE THE DRAWING	2018.10.17	x.xx±0.25	ANGLE±
A0	NEW RELEASE	2005.07.01	x.xx±0.20	
REV	DESCRIPTION	DATE	x.xxx±0.15	


Title :		2.54mm PITCH
		Crimp Flex Housing
DRAW NO :	A2550H-XP-A	REV A1



4P~25P



2P



3P

