




SPECIFICATIONS:

Current Rating: 3A AC,DC
Voltage Rating: 300V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 5mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1100V AC/minute
Material: PBT30%GF,UL94V-0(Blue)

Ordering Information & Dimensions

Circuits	Dimensions(mm)			Circuits	Dimensions(mm)		
	A	B	C		A	B	C
2P	2.54	6.81	10.16	14P	33.02	37.29	40.64
3P	5.08	9.35	12.70	15P	35.56	39.83	43.18
4P	7.62	11.89	15.24	16P	38.10	42.37	45.72
5P	10.16	14.43	17.78	17P	40.64	44.91	48.26
6P	12.70	16.97	20.32	18P	43.18	47.45	50.80
7P	15.24	19.51	22.86	19P	45.72	49.99	53.34
8P	17.78	22.05	25.40	20P	48.26	52.53	55.88
9P	20.32	24.59	27.94	21P	50.80	55.07	58.42
10P	22.86	27.13	30.48	22P	53.34	57.61	60.96
11P	25.40	29.67	33.02	23P	55.88	60.15	63.50
12P	27.94	32.21	35.56	24P	58.42	62.69	66.04
13P	30.48	34.75	38.10	25P	60.96	65.23	68.58

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet
mm	5:1	1 of 1
Draw BY:		Approved :
Tony Su		Jack Yin

Title :

2.54mm PITCH

Crimp Flex Housing

DRAW NO : A2550H-XP-D

REV
A1

REV	DESCRIPTION	DATE
A1	CHANGE THE DRAWING	2018.03.14
A0	NEW RELEASE	2005.07.01

General Tolerance	
x.xx±0.25	ANGLE±
x.xx±0.20	
x.xxx±0.15	