





SPECIFICATIONS:

Current Rating: 3A AC,DC
Voltage Rating: 300V AC,DC
Temperature Range: -40°C ~ +105°C
Contact Resistance: 5mΩ Max
Insulation Resistance: 1000MΩ Min
Withstanding Voltage: 1100V AC/minute
Material: PBT30%GF,UL94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2x2P	2.54	5.08	2x14P	33.02	35.56
2x3P	5.08	7.62	2x15P	35.56	38.10
2x4P	7.62	10.16	2x16P	38.10	40.64
2x5P	10.16	12.70	2x17P	40.64	43.18
2x6P	12.70	15.24	2x18P	43.18	45.72
2x7P	15.24	17.78	2x19P	45.72	48.26
2x8P	17.78	20.32	2x20P	48.26	50.80
2x9P	20.32	22.86	2x21P	50.80	53.34
2x10P	22.86	25.40	2x22P	53.34	55.88
2x11P	25.40	27.94	2x23P	55.88	58.42
2x12P	27.94	30.48	2x24P	58.42	60.96
2x13P	30.48	33.02	2x25P	60.96	63.50

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet	TITLE		
mm	3:1	1 of 1			
DRAWN	CHKD	APPR	2.54mm PITCH Housing		
Chengbiao Ye	Djankui Wan	Jack Yin			
General Tolerances		THIRD ANGLE PROJECTION	DRAWING NO. A2550HA-2xXP		REV A1
x.xx±0.25 x.xxx±0.20 x.xxxx±0.15 ANGLES ±1°					

A1	CHANGE THE DRAWING	2023.03.10
A0	NEW RELEASE	2005.07.01
REV	DESCRIPTION	DATE