



P.C.B LAYOUT
TOLERANCE:±0.05

Ordering Information:

A3961WVB-F-XP - ^{**} - ^{***}

1 2 3

1. Part NO.

2. Material:

(Blank): Nylon 66, UL94V-0 (White)

GWT: Nylon 66, UL94V-0 (Beige),

IEC 60335-1, 5th Edition

Glow Wire Capable.

3.Finish:

(Blank): Tin over Nickel

G: Gold over Nickel

G10: Gold over Nickel (Au:10u"Mating area)

G15: Gold over Nickel (Au:15u"Mating area)

G30: Gold over Nickel (Au:30u"Mating area)

SPECIFICATIONS:

Current Rating: 7A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1500V AC/minute

Pin Material: Brass

Material: Nylon 66,UL94V-0

Ordering Information & Dimensions

Part NO.	Dimensions(mm)	
	A	B
A3961WVB-F-2P	3.96	7.92
A3961WVB-F-3P	7.92	11.88
A3961WVB-F-4P	11.88	15.84
A3961WVB-F-5P	15.84	19.80
A3961WVB-F-6P	19.80	23.76
A3961WVB-F-7P	23.76	27.72
A3961WVB-F-8P	27.72	31.68
A3961WVB-F-9P	31.68	35.64
A3961WVB-F-10P	35.64	39.60
A3961WVB-F-11P	39.60	43.56
A3961WVB-F-12P	43.56	47.52
A3961WVB-F-13P	47.52	51.48
A3961WVB-F-14P	51.48	55.44
A3961WVB-F-15P	55.44	59.40
A3961WVB-F-16P	59.40	63.36
A3961WVB-F-17P	63.36	67.32
A3961WVB-F-18P	67.32	71.28
A3961WVB-F-19P	71.28	75.24
A3961WVB-F-20P	75.24	79.20

CJT *continues*

CHANGJIANG CONNECTORS CO.,LTD.

Unit	Scale	Sheet	TITLE 3.96mm PITCH VERTICAL WAFER	
mm	3:1	1 of 1		
DRWN	CHK'D	APPR		
Wennin Luo	Diankuí Wan	Jack Yin		
General Tolerances		THIRD ANGLE PROJECTION		
x,xxx±0.25 x,xxx±0.20 x,xxx±0.15 ANGLES ±1°			DRAWING NO.	REV
			A3961WVB-F-XP	A2