




Ordering Information:


C1581HFB-XP - $\frac{**}{2}$

1.Part NO.



2.Material:

(Blank): Nylon 66,UL94V-2(Natural)

V0: Nylon 66,UL94V-0(White)



Panel hole layout



SPECIFICATIONS:

Current Rating:5A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 10mΩ Max

Insulation Resistance: 1000MΩ Min

Withstanding Voltage: 1500V AC/minute

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	3.68	8.62	4P	11.04	15.98
3P	7.36	12.30	5P	14.72	19.66

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit		Scale		Sheet		TITLE			
mm		2.5:1		1 of 1					
DRAWN		CHK'D		APPR		3.68mm PITCH HOUSING			
Chengbiao Ye		Diankui Wan		Jack Yin					
General Tolerances		THIRD ANGLE PROJECTION 		DRAWING NO. C1581HFB-XP				REV A1	
x.xx±0.25 x.xx±0.20 x.xxx±0.15 ANGLES ±1°									
5									
0									
REV									

x.xx±0.25
x.xxx±0.20
x.xxxx±0.15
ANGLES ±1°

