







Ordering Information:

D2541WR-XP-2 - *
1 2

1.Part No.

2.Logo & Marking

(Blank): With Mark

NK: Without Mark

SPECIFICATIONS:

Current Rating: 3A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 20mΩ Max.

Insulation Resistance: 1000MΩ Min.

Withstanding Voltage: 1500V AC/minute

Material: Nylon 46, UL 94V-0(Black)

Pin Material:Brass/Tin over Nickel

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	2.54	7.21	14P	33.02	37.69
3P	5.08	9.75	15P	35.56	40.23
4P	7.62	12.29	16P	38.10	42.77
5P	10.16	14.83	17P	40.64	45.31
6P	12.70	17.37	18P	43.18	47.85
7P	15.24	19.91	19P	45.72	50.39
8P	17.78	22.45	20P	48.26	52.93
9P	20.32	24.99	21P	50.80	55.47
10P	22.86	27.53	22P	53.34	58.01
11P	25.40	30.07	23P	55.88	60.55
12P	27.94	32.61	24P	58.42	63.09
13P	30.48	35.15			

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit		Scale		Sheet		TITLE	
mm		4:1		1 of 1		2.54mm IDC 90° Wafer	
DRAWN		CHK'D		APPR			
Chengbiao Ye		Diankui Wan		Jack Yin			
General Tolerances				THIRD ANGLE PROJECTION		DRAWING NO.	
x,xx±0.25						D2541WR-XP-2	
x,xxx±0.20							
x,xxxx±0.15							
ANGLES ±1°							
1						REV A0	

A0	NEW RELEASE	2005.07.01
REV	DESCRIPTION	DATE