



P.C.B LAYOUT
TOLERANCE:±0.05

Ordering Information:

D2541WV-XP - *
1 2

1.Part No.




2.Finish:

(Blank):Tin over Nickel

G:Gold over Nickel

G15:Gold over Nickel(Au:15u",Mating Area)

G30:Gold over Nickel(Au:30u",Mating Area)



SPECIFICATIONS:

Current Rating: 3A AC,DC

Voltage Rating: 250V AC,DC

Temperature Range: -40°C ~ +105°C

Contact Resistance: 20mΩ Max.

Insulation Resistance: 1000MΩ Min.

Withstanding Voltage: 1500V AC/minute

Pin Material:Brass/Tin over Nickel

Material: Nylon 46, UL 94V-0(Black)

Ordering Information & Dimensions

Circuits	Dimensions(mm)		Circuits	Dimensions(mm)	
	A	B		A	B
2P	2.54	7.21	14P	33.02	37.69
3P	5.08	9.75	15P	35.56	40.23
4P	7.62	12.29	16P	38.10	42.77
5P	10.16	14.83	17P	40.64	45.31
6P	12.70	17.37	18P	43.18	47.85
7P	15.24	19.91	19P	45.72	50.39
8P	17.78	22.45	20P	48.26	52.93
9P	20.32	24.99	21P	50.80	55.47
10P	22.86	27.53	22P	53.34	58.01
11P	25.40	30.07	23P	55.88	60.55
12P	27.94	32.61	24P	58.42	63.09
13P	30.48	35.15			

CJTconn

CHANGJIANG CONNECTORS CO.,LTD.

Unit		Scale		Sheet		Title : 2.54mm IDC	
mm		4:1		1 of 1			
Draw By:				Approved :			
Diankui Wan				Jack Yin			
General Tolerance						180° Wafer	
x.x±0.25 x.xx±0.20 x.xxx±0.15		PROJECT					
1				DRAW NO : D2541WV-XP		REV A0	